



Technical Data Sheet

WT

General Description

- A 50% water dispersion of GWT pigments.
- Daylight and ultra-violet responsive fluorescent pigment dispersion free of formaldehyde for water based formulations.
- A dyed/pigmented thermoplastic polyester amide copolymer in dispersion.

Applications

Water based formulations: paints, paper- and textile inks.

Product Features

- Free of formaldehyde.
- WT water dispersions are easy mixable and require no additional grinding for proper dispersion into the binder system.
- Öko-Tex Standard 100: testing for compliance on end application is recommended.
- For aqueous formulations, the use of preservatives is highly recommended. The right preservative package (combination of bactericides and fungicides) should provide reliable, highly effective control of microorganisms in the intended formulation.
- Limited lightfastness in exterior exposure due to the chemical structure of the fluorescent pigments.

| Standard Colors | |
|-----------------|-------------|
| Product Name | Description |
| WT-10 | Chartreuse |
| WT-11 | Green |
| WT-13 | Orange |
| WT-14 | Orange Red |
| WT-15 | Red |
| WT-16 | Cerise |
| WT-17 | Pink |
| WT-18 | Magenta |
| WT-88 | Purple |

Packaging:

1 Pail = 50 kgMOQ = 200kg

Storage & shelf life:

6 months when kept in closed original packaging in a dry place at ambient temperature. Dispersion should be protected from freezing.

Safety & regulatory:

Safety Data Sheet available on request.

| Physical properties | |
|-----------------------|-----------------------------------|
| Delivery form | Liquid |
| Average particle size | ± 4 µm |
| Hegman grind | 5.0 – 6.0 |
| Viscosity | 150 – 180g (200RPM Stormer-Krebs) |
| Solids | 50.0 – 51.5 % |
| Specific gravity | 1.0 – 1.15 g/ml |

Test methods and Certificate of Analysis (COA) available on request.

| Processing | |
|---|---|
| Heat stability | Limited. |
| Solvent resistance | Recommended use in water, addition of co-solvents should be carefully tested. |
| WT water dispersions offer good storage stability. However, it is advisable to homogenize | |

the dispersion before use.

WT dispersions are designed for use at industrial sites as described in EU COMMISSION REGULATION 2023/2055 of 25 September 2023.

Disclaimer: Our technical advice, information, statements, whether given verbally, in writing, or in the form of test results, is offered for your guidance without warranty. No warranty for fitness for a particular purpose is made. This also applies where protective rights of third parties are involved. It does not release the user from obligation to test the suitability of the products and formulas for the intended process and applications. Our guarantee is limited to the consistent quality of our product. Rev:1.3 22-Dec-23