

# Technical Data Sheet

## C-09

### General Description

- Ultra-violet responsive fluorescent pigments for water and nonpolar solvent based formulations.
- A dyed/pigmented thermoplastic sulphonamide-melamine-paraformaldehyde resin.

### Applications

- UV Blue tracer for aqueous paper coating, water and non-polar solvent based paints and textile printing inks.

### Product Features

- C-09 is relatively invisible in normal daylight, but produces a highly visible and vibrant blue color upon exposure to ultra-violet or "black" light.
- Popular for security and tracing applications like counterfeit protection, product identification and process automation.
- For aqueous formulations, the use of preservatives is recommended. The right preservative package (combination of bactericides and fungicides) should provide reliable, highly effective control of microorganisms in the intended formulation.

### Standard Color

Product Name	Description
C-09	UV Blue

#### Packaging:

1 box = 20kg (2x10kg)  
MOQ = 20kg

#### Storage & shelf life:

120 months when kept in closed original packaging in a dry place at ambient temperature.

#### Safety & regulatory:

Safety Data Sheet available on request.

### Physical properties

Delivery form	Powder
Particle size (Laser diffraction)	± 3.0 µm
Hegman grind	5.0 - 6.0
Melting point	110 – 130°C
Decomposition temp.	>300°C
Specific gravity	1.35 – 1.40 g/ml
Bulking value	0.25 g/ml
Oil absorption	60

(1) Test methods and Certificate of Analysis (COA) available on request.

### Processing

Heat stability	Limited
Solvent resistance	Recommended use in water, aliphatic- and some aromatic hydro carbons.
Pigments are insoluble and need to be dispersed (easily stir-in).	
Adding C-09 (UV Blue) will purify the color and will increase the UV-response.	

Disclaimer: Our technical advice, information, statements, whether given verbally, in writing, or in the form of test results, is offered for your guidance without warranty. No warranty for fitness for a particular purpose is made. This also applies where protective rights of third parties are involved. It does not release the user from obligation to test the suitability of the products and formulas for the intended process and applications. Our guarantee is limited to the consistent quality of our product.