

Technical Data Sheet

P-X-0936

General Description

- Ultra-violet responsive fluorescent pigments for solvent based formulations.
- A dyed/pigmented thermoset sulphonamide-melamine-paraformaldehyde resin.

Applications

- UV Green tracer for calendered PVC foils, PVC & PU coatings, solvent based paints, screen - and gravure inks, aerosols.

Product Features

- P-X-0936 is relatively invisible in normal daylight, but produces a highly visible bright and vibrant green color upon exposure to ultra-violet or "black" light.
- Popular for security and tracing applications like counterfeit protection, product identification and process automation.
- For aqueous formulations, the use of preservatives is recommended. The right preservative package (combination of bactericides and fungicides) should provide reliable, highly effective control of microorganisms in the intended formulation.

Standard Color

Product Name	Description
P-X-0936	UV Green

Packaging:

1 box = 20kg (2x10kg)

MOQ = 20kg

Storage & shelf life:

120 months when kept in closed original packaging in a dry place at ambient temperature.

Safety & regulatory:

Safety Data Sheet available on request.

Physical properties	
Delivery form	Powder
Particle size (Laser diffraction)	± 5.0 µm
Hegman grind	5.0 - 6.0
Melting point	Thermoset, non-melting
Decomposition temp.	>300°C
Specific gravity	1.40 g/ml
Bulking value	0.25 g/ml
Oil absorption	56

(1) Test methods and Certificate of Analysis (COA) available on request.

Processing	
Heat stability	In PVC calendering: 30 minutes @ 170°C
Solvent resistance	Recommended use in water, aliphatic- and aromatic hydrocarbons, alcohols, esters, glycols, plasticizers.
Pigments are insoluble and need to be dispersed (easily stir-in).	
Adding P-09 (UV Blue) will purify the color and will increase the UV-response.	

Disclaimer: Our technical advice, information, statements, whether given verbally, in writing, or in the form of test results, is offered for your guidance without warranty. No warranty for fitness for a particular purpose is made. This also applies where protective rights of third parties are involved. It does not release the user from obligation to test the suitability of the products and formulas for the intended process and applications. Our guarantee is limited to the consistent quality of our product.