

Technical Data Sheet

PAP

General Description

- Daylight and ultra-violet responsive fluorescent plastic colorants - free of formaldehyde - for the paper coating industry.
- A dyed/pigmented thermoplastic polyamide-ester resin.

Applications

- Recommended for extrusion, injection moulding, blow moulding, film blowing etc.

Product Features

- PAP offers bright colors for applications where safety and high visibility is required.
- PAP has no formaldehyde outgassing and is odorless during its transformation.
- PAP has the advantage of a low level of migration, whereby both heat stability and light resistance are optimized.
- For aqueous formulations, the use of preservatives is highly recommended. The right preservative package (combination of bactericides and fungicides) should provide reliable, highly effective control of microorganisms in the intended formulation.

Standard Colors

Product Name	Description
PAP-3-0933	Orange
Packaging: 1 box = 20kg MOQ = 20kg	
Storage & shelf life: 120 months when kept in closed original packaging in a dry place at ambient temperature.	
Safety & regulatory: Safety Data Sheet available on request.	

Physical properties	
Delivery form	Powder
Particle size (Laser diffraction)	8.0 – 15.0 µm
Decomposition temp.	>300°C
Specific gravity	1.20 g/ml
Bulking value	0.3 – 0.4 g/ml

(1) Test methods and Certificate of Analysis (COA) available on request.

Processing
PAP Fluorescent pigments are semi-transparent. For this reason printing on a white coated surface is recommended to obtain the maximal fluorescent effect.
Pigments are insoluble and need to be dispersed (easily stir-in).