

# Technical Data Sheet

## RBAG-09

### General Description

- Ultra-violet responsive fluorescent ink base – free of mineral oils – for solvent based inks.
- A dyed/pigmented thermoplastic sulphonamide-melamine- paraformaldehyde carrier, dispersed in an alkyd resin.

### Applications

- UV Blue tracer for offset & letterpress inks.

### Product Features

- Highly viscous sub-micron ink base – free of mineral oils – which needs to be converted into finished offset ink. Adding 20% - 30% printing vehicles, driers and additives are necessary.
- Recommended for oxidation or heat-set drying ink formulations.
- Formulation with an UV curing system is possible.
- RBAG-09 is colorless in normal daylight, but glows blue under UV exposure, making it especially suitable as a tracer.
- Compatible with conventional inks to enlarge the available color space to create new and brighter shades.
- RBAG exhibit good lightfastness for indoor application, while the exterior lightfastness is rather limited.

### Standard Colors

Product Name	Description
RBAG-09	UV Blue

#### Packaging:

1 metal pail = 20kg  
 1 metaal drum = 200kg  
 MOQ = 20kg

#### Storage & shelf life:

36 months after production date when kept in closed original packaging in a dry place at ambient temperature.

#### Safety & regulatory:

Safety Data Sheet available on request.

### Physical properties

Delivery form	Paste
Pigment concentration	> 50%
Average particle size	Sub-micron
Hegman grind	≥ 6.0
Specific gravity	1.15 g/ml
Laray viscosity	> 3500 Poise

(1)Test methods and Certificate of Analysis (COA) available on request.

### Processing

Adding RBAG-09 will purify the color and increase the UV response.

Disclaimer: Our technical advice, information, statements, whether given verbally, in writing, or in the form of test results, is offered for your guidance without warranty. No warranty for fitness for a particular purpose is made. This also applies where protective rights of third parties are involved. It does not release the user from obligation to test the suitability of the products and formulas for the intended process and applications. Our guarantee is limited to the consistent quality of our product.